



(An ISO 9001:2008 Company)

www.twinindia.com

sales@twinindia.com

2222 D/S POLYESTER TAPE

2222 D/S POLYESTER TAPE : It is transparent double sided adhesive tapes consist of transparent polyester film with modified acrylic adhesive system. It has an easy release paper liner. The tape is very thin and offers a good tack and high shear resistance hence ideal for splicing application. Red color is also available on demand.

Applications : Mounting of badges and signs made of metal or plastic, splicing of thin plastic or metal films, used for core starting application bin film manufacturing & processing units, for manual splicing of films like polyester or BOPP at reeler & rewinding station of film manufacturing and processing units.



#2224 D/S CLOTH TAPE

#2224 D/S CLOTH TAPE : This tape is made out of cloth and is coated on both sides with strong natural rubber adhesive which also has masking properties. This tape is laminated with polyester or paper release liner. This tape is also called Plate Mounting (Flexo Printing) tape. By using this tape the flexo printing quality is enhanced and dot gain is reduced.

Application : Mounting of rubber plates, mounting of photo- polymeric plates, fixing of uneven surfaces such as felt and carpets mounting stereos and joining dissimilar material etc.etc.



2226 FLOOR MARKING TAPE

2226 FLOOR MARKING TAPE : It is a plasticized PVC tape coated with an aggressive modified rubber-resin adhesive, which is lead free, good adhesion to most surfaces, distinct colors code for safety warning and marking, remove without adhesive residue. It also has good resistance to solvent, oil and water. Floor Marking Tape is available in multi colors: RED, WHITE, YELLOW, BLUE, GREEN, ZEBRA (Yellow/Black).

Applications : It is suitable for line marking to delineate lanes & opening, hazard warning to identify potential risk area & safety zone.



2228 DUCT TAPE

2228 DUCT TAPE : It is a polyethylene laminated mesh cloth adhesive tape with high flexibility and conform ability. This tape is suitable for duct work and general purpose. It is widely used in Aerospace, Automotive, Electrical, Heating Ventilation and Air conditioning (HVAC) and Construction industries. It has good adhesion even on rough surfaces, waterproof and easy to tear by hand.

Applications : sealing of ducts, fastening of protection films, closing of covering foils, especially in the field of asbestos removal, sealing of rubbish bags, fixing, closing, packaging and a lot more etc.



2230 CELLOPHANE TAPE

2230 CELLOPHANE TAPE : It is a clear transparent tape with cellulose film and natural rubber adhesive. The tape comes off without leaving any adhesive residue. Cellophane tape can be torn by hand and is convenient to use without a dispenser.

Applications : Packaging, covering and masking, film splicing, temporary holding of laminates, holding of yarn in power loom, plastic film welding etc.



2232 MASKING TAPE (GP)

2232 MASKING TAPE (GP) : It is an economical creped paper tape suitable for general purpose masking, bundling, holding, sealing and surface protection applications. It is recommended as a light duty packaging tape. It is residue free when removed.

Application : Masking, labeling, sealing, holding and light duty packaging. It is used for masking the area where the paint should not be sprayed at the time of painting.



2234 SURFACE PROTECTION TAPE

2234 SURFACE PROTECTION TAPE : Self-adhesive surface protection tape has excellent protection against damages and scratches. This tape has adjustable peeling force, no adhesive residue and weather resistant. Thickness from 30 micron to 100micron. Available in Clear, White and Black-White colors.

Application : Surface protection of plastic components, painted sheet metal components, ABS components, glass, laminated wood, panels, powder coated surface and many more.



2320 BOPP TAPE

2320 BOPP TAPE : Biaxially Oriented Polypropylene (BOPP) Film coated with acrylic based adhesive in different micron (gsm) coating thickness. The BOPP tape is available in different colours. BOPP tape is used in carton box sealing and for stationery purpose. Printing of single and multiple colour is also possible with logo or customized design. Company name, logo, contact details and customized messages can be printed on tape to communicate quality & professionalism.



2238 PINK RAYON TAPE

2238 PINK RAYON TAPE : This tape is used for coil winding, holding wires in motors, telephones & telecommunication equipments, in core insulation, relay & transformers solenoid coils etc. It is excellent for edging slot insulation, securing terminal saddle to transformer coil, holding down wire leads in corrosive environment.



2240 SILICONIZED KRAFT PAPER TAPE

2240 SILICONIZED KRAFT PAPER TAPE : This is made of kraft paper coated with natural rubber adhesive that exhibits high adhesion and good shear properties. This double sided construction increases the tapes mechanical strength while siliconizing reinforces its resistance to moisture and water. It is 100% biodegradable.

Application : Sealing carton and general packaging purpose. Suitable for cold storage or humidity conditions packing. Non-repulpable splicing, core starting and end tabbing. Towing electrical and mechanical parts for conversion. Used in silk screening & picture framing.



SF-555 SILICON SELF FUSING HT TAPE

SF-555 SILICON SELF FUSING HT TAPE : Silicone Self-Fusing Tape (High Temperature Self-Fusing Insulation Tape): Silicone Rubber Self-Fusing Tape is a high performance, extruded wrapping tape. No adhesive is required. SSF Tape is self-adhering, self-fusing and permanent. It fuses in minutes and cures in 24 hours at room temperature. Faster curing and a harder finish is accomplished by applying heat after wrapping. Temperature range is 60°C to 250°C for continuous use; -65°C to +260°C for intermittent use. Break down voltages 33.6KV. Silicone Self-Fusing Tape is tough, permanently resilient, insulating and void-free. SSF is strong, elastic and conforming. It is ideal for automatic wrapping. It protects from effects of vibration and shock. It will not crack or separate with expansion or contraction stress. This product is amazingly useful.

Size: 1ROLL 25.4MM X 0.508MM X 12 YARDS

Application : Automatic wrapping electrical insulation, moisture protection, high or low temperature applications. SSF is thermally conductive which allows generated heat to dissipate rapidly. Used in Military, aerospace, industrial motor and marine applications including utility cable terminations and splices, bus bar insulation, motor coil terminal connections, and fuel line and hose repair. Replacement of heat shrinkable tapes/sleeves. SSF can even be applied UNDERWATER! Silicone Self-Fusing Tape tape is the perfect alternative to adhesive electrical tape, duct tape, and heat shrink tape for many applications. It withstands UV Rays, acids, weather, water and Ozone.



2223 D/S TISSUE TAPE

2223 D/S TISSUE TAPE : it is a double sided mounting tape equipped with a light weight tissue paper backing and coated with an acrylic adhesive of very high tack and resistant to light and aging. This tape is used in shoe and leather industry, foam industry, postal service, decoration, label and lot of other uses.

Applications : Lamination of nameplates and logos, fixing of front fascia plate, mounting of plastic door linings in the car industry, fixing of garment labels.



2225 D/S FOAM TAPE

2225 D/S FOAM TAPE : This tape is made out of foam of PE, PU, PVC and EVA coated with various types of adhesive for various applications. It is used in refrigeration, stationery, die-cut, impact preventing material or adheres with advertising sign board and plates and various other applications.

This tape is available in different thicknesses 0.4mm, 0.8mm, 1mm, 2mm, 3mm etc.

Applications : It is used in refrigeration, stationery, die-cut, impact preventing material or adheres with advertising sign board and plates and various other applications. This tape is available in different thicknesses.



2227 ALUMINUM FOIL TAPE

2227 ALUMINUM FOIL TAPE : It is a specialty tape designed for mounting of refrigeration coils and other similar applications. It is a dead-soft aluminium foil tape coated with a modified acrylic adhesive system and with an easy-release paper liner. It is highly conformable resulting in easy application over the refrigeration coils without rupturing. The adhesive system is stable over wide temperature range, making it ideal for application in refrigerator, coolers, etc. It acts as an excellent barrier to moisture and prevents damage to the coils from PUF.

Applications : Holding of condenser / evaporator coils in refrigerators, moisture barrier, around windows in luxury buses & in appliances, general purpose heat reflector, mechanical holding of wires in appliances walls etc.



2229 FILAMENT TAPE (MONO & CROSS) :

2229 FILAMENT TAPE (MONO & CROSS) : This tape has fiberglass reinforced backing, very high tensile strength and not easy to break. It can be used against steel straps for heavy duty packing and mounting of articles in white good industry. Mono filament tape is also used as holding tape in refrigerators because it is residue free and so while removing the tape, the adhesive will not get transferred.

Applications : Bundling and strapping heavy goods, securing pallets, closing and reinforcing of shipping cartons.



2231 DOOR HOLDING TAPE

2231 DOOR HOLDING TAPE : It is a medium duty strapping / securing tape. It is specially designed tape with a unique natural rubber adhesive system, which is stain and adhesive transfer resistant, clean removal from the plastic surface even after a long period of storage.

Applications : Closing, holding and securing in the appliance / furniture industry / packaging. It is used during manufacturing of appliances (in process) and during transportation for securing against damage.



2233 MASKING TAPE (HT)

2233 MASKING TAPE (HT) : A premium crepe paper masking tape exhibits excellent adhesion, tack & good cohesion strength. The adhesive is a specially formulated rubber based for high temp. applications up to a temperature of 90C, 110C & 160C. It also has good resistance to solvents, oil and water.

Application : Masking for automotive components, marine applications, masking for circuit boards, final bandage of coils for electrical motors, mild powder coating etc.



2235 PVC INSULATION TAPE

2235 PVC INSULATION TAPE : PVC Insulating Tape is produced from soft PVC film primarily for electrical insulation purposes. It is also used for binding of electrical tools, manufacturing of automobile harness, anti-magnetic coil and various other purposes. Available in RED, YELLOW, BLUE, BLACK, GREEN colors in standard length of 10mtrs & 20mtrs.

Application : Electrical insulation, cable harnessing industries in relation to automotive segments.




2237 KAPTON TAPE

2237 KAPTON TAPE : Kapton tapes are ideal for masking gold contacts and protecting plug-in connectors & switches during wave soldering. These products have been found to give a better performance than mechanical masks & other tapes. It is suitable for most wave soldering.

Comfortable to irregular surfaces.

Resistance to high chemical attack and excellent electrical insulation. Ideal for wave soldering, insulation circuit board, high temp. Powder coatings.



2239 VHB TAPE

2239 VHB TAPE : Provides the convenience and simplicity of a tape fastener and are ideal for use in many interior and exterior bonding applications. In many situations, they can replace rivets, spot welds, liquid adhesives and other permanent fasteners. These tapes are made with acrylic foam which is viscoelastic in nature. This gives the foam energy absorbing and stress relaxing properties which provides this tape with their unique characteristics. The acrylic chemistry provides outstanding durability performance.



2241 Cotton Cloth Tape

2241 Cotton Cloth Tape : This tape is coated with special water proofing compound on outside and PSS adhesive spread inside. It is used extensively in packaging fields for various applications, has excellent adhesive properties and does not dry. It is a must for all packaging, maintenance and holding jobs. This tape is available in black and white colors.



SF-556 TAPE (Self Amalgamating Insulating Tape)

SF-556 TAPE (Self Amalgamating Insulating Tape) : Self amalgamating insulating tape is specially prepared for electrical & electronic industries, Panel makers, Projects, Electrical contractors, electrical utilities etc. Excellent electrical properties such as superior volume resistivity, higher breakdown voltage. Excellent resistance to polluted atmosphere, saline water and weather. Excellent self amalgamating properties & exceptional ozone resistance. Beneficial when compared with PVC heat shrinkable sleeves or PVC tape. It will not crack or separate with expansion or contraction stress. This product is amazingly useful. Break down voltages 53 KV.

SIZE: 1ROLL 38MM X 0.76MM X 9.1 mtrs.

Application : Clean & degrease the surface thoroughly by using any solvent residueless cleaner. The tape contains plastic liner Stretch 25-30% & wrap with moderate tension with half overlap. Apply last lap with zero stretch. Press down to avoid end lifting before fusion takes place. The tape will start amalgamating within 1-2 hours and full amalgamating within 24 hours.



Manufactured By :-



TWIN TECH India Pvt. Ltd.

(An ISO 9001:2008 Company)

H-75 A, Sector-12, Pratap Vihar, Ghaziabad - 201009 (U.P.)

Ph : 0120-2840276, 2841949, 6545141 Fax : 0120-2840723

E-mail : sales@twinindia.com Web : www.twinindia.com

Factory : R-51-52, UPSIDC, Sikandrabad, Uttar Pradesh (INDIA)

Authorised Distributor